



# AQT-900

Generating Set  
**TECHNICAL DATA SHEET**

### Standard Specifications:

- 1 Prime Rating:  
 Unlimited hours usage, with an average load factor of 80% over each 24 hour period. 10% overload is available for 1 hour in every 12 hours operation.  
 o overload is permitted on standby power.
- 2 Standby Rating:  
 Limited to 500 hours annual usage, with an average load factor of 80% of the published standby power rating over each 24 hour period. Up to 300 hours of annual usage may be run continuously.  
 No overload is permitted on standby power.
- 3 Engine:  
 Perkins, including air filters, fuel filters, oil filter, starting motor and charging alternator etc.
- 4 Alternator Type:  
 brushless AC alternator
- 5 Radiator:  
 50°C, fan protective shroud

### Output Rating:

PRIME:		STANDBY:	
50 Hz—1500 Rpm	400 V, 3ph		
802 kVA	641 kW	900 kVA	718 kW
60 Hz—1800 Rpm	480 V, 3ph		
849 kVA	679 kW	944 kVA	755 kW

### ENGINE SPECIFICATIONS

Engine Make	PERKINS
Engine Model	4006-23TAG3A
No. of Cylinders	6 vertical in-line
Cycle	4 Stroke
Aspiration	Turbocharged & air to air charged cooled
Cooling Method	Water cooled
Governing Type	Electronic
Governing Class	G2 - ISO 8528 Part 1
Compression Ratio	13.6;1
Displacement	22.9 L
Bore/Stroke	160 x 190 mm
Dynamic Charging Alternator	55AMP, 24V

### ALTERNATOR SPECIFICATIONS

Alternator Make	Leroy Somer   STAMFORD   AQT
Alternator Model	TAL-049-C
Number of Poles	4
Number of Winding Leads	6
Type of Bearing	Single Bearing
Insulation Class - Temp Rise	Cont. H - 125/40 C
Ingress Protection Rating	IP 23
Excitation System	Self Excited
AVR Model	R150

### Comply with Standards

ISO 3046, BS 5514, DIN 6271, NEMA-MGI, DIN EN, BS 5000, IEC 60034, IEC 60947-2

### Alternator Operating data

Over speed	2250 rpm
Voltage Regulation	± 1%
Harmonic Coefficient THF	< 2%
Tel. influence TIF	< 50
Cooling air flow	1.0 m <sup>3</sup> /Sec

### Powered By:



Diesel Generator



LEROY-SOMER



## Standard Specifications:

### 6- Fuel Tank:

Capacity of fuel tank is for 8 hours running  
Built in fuel tank up to 800 kVA

### 7- Circuit Breaker:

3 pole LS MCCB

### 8- Control system alarms:

- Over and Under Speed
- Low and High Battery Volt.
- Start and Stop Failure
- Over Current
- Under / Over Generator Voltage
- Low Oil Pressure
- Emergency stop
- High engine temperature

### 9- Warranty policy:

- AQT GENERATOR products has a warranty for 12 Months or 1000 hours whichever occurs first against any manufacturing defects
- Wearing parts (filters), incorrect man made operation, maintenance failures are excluded from the warranty policy

## Acoustic Enclosure Specifications:

Enclosure Type	Acoustic & Weather Proof
Drainage	Fuel and Water Drainage
Transportation	Tested Single Point Lifting Facility & Forklift Pockets
Ingress Protection Rating	IP 23
Lifting	ISO Standard Lifting
Canopy RAL Color	TAL 9010
Base frame RAL Color	RAL 9011
Noise Pressure level @ 7m	78db(A) @ 7 mt

## Control System:

Large back-lit text display  
(4-Line back-lit LCD text display)  
Multiple display languages  
DSENet® expansion compatible  
Data logging facility  
Fully configurable via PC using USB communication  
Front panel configuration  
Efficient power save mode  
3 phase generator sensing  
Accumulated power monitoring (kW h, kVA h, kVAr h)  
Generator/load current monitoring and protection  
Generator overload protection (kW)  
Breaker control via fascia buttons

Fuel and start outputs, configurable when using CAN  
8 configurable DC outputs  
9configurable analogue/digital inputs  
Automatically transfers between mains (utility) and generator (DSE7320 MKII only)  
Increased input and output expansion capability via DSENet®  
IP65 rating (with optional gasket) offers increased resistance to water ingress  
DIGITAL INPUTS  
ANALOGUE INPUT



**DSE7320 MKII**  
AUTO START & AUTO MAINS  
FAILURE CONTROL

## Dimensions:

Type	Length (mm)	Width (mm)	Height (mm)	Fuel Tank (L)	Weight (KG)
OPEN	4300	1750	2200	1170	6300
CLOSED	6000	2440	2590	1170	9300



## Engine:



Perkins heavy duty high performance industrial type diesel engine.

### COOLING SYSTEM

Total Coolant Capacity (L)	105 L
Cooling Fan Air Flow	870 m <sup>3</sup> / min
Radiator Fan Load	26 kW
Heat Radiation to Room (PRP)	77 kW
Heat Radiation to Room (ESP)	86 kW

### LUBRICATION SYSTEM

Oil Filter Type	Spin-On Full Flow
Total Oil Capacity	113.4 L
Oil Type	API-CH-4 or ACEA E5

### EXHAUST SYSTEM

Muffler Type	Industrial Grade
Max. Back Pressure	6 kPa
Exhaust Gas Flow (PRP/ESP)	193 m <sup>3</sup> / min
Exhaust Gas Temperature	≤ 500 °C

### FUEL SYSTEM

Recommended Fuel	Class A2 Diesel
Fuel Consumption Standby	194 L/hr
Fuel Consumption 100% PRP	172 L/hr
Fuel Consumption 75% PRP	137 L/hr
Fuel Consumption 50% PRP	130 L/hr

### AIR SYSTEM

Air Filter Type	Paper Element
Combustion Air Flow (PRP)	69 m <sup>3</sup> /min
Combustion Air Flow (ESP)	73 m <sup>3</sup> /min
Max Air Filter Intake Restriction	3.7 kPA

## Optional configurations:

### Engine accessories:

- Heavy-duty air filter
- Coolant heater
- Lubricant oil heater
- Fuel and Water Separator
- Lube oil rotary pump

### Alternator And Accessories:

- Leroy somer/stamford
- Anti condensation heater
- PMG + AVR ⇄Double bearing alternator
- High voltage\_\_\_\_\_kV
- RTDs for Bearing and winding

### Cooling System:

- 55 degree Radiator
- Remote Radiator

### Control System:

- AMF
- Parallel
- Practical type in low temperature environment
- Control Screen Heater
- Remote Annunciators
- Other (ComP, DEIF)

### Circuit Breaker:

- 3/4 poles
- Fixed/handcart type
- Electric mechanism

### Automatic Transfer Switch (ATS):

- ATS cabinet
- Contractor type ATS
- Motorized changeover type ATS

### Start Battery:

- Nickel-cadmium battery
- Maintenance-free battery
- Battery charger and selector switch
- Charging current meter

### External Fuel Tank:

- Single /double wall fuel tank (500-5000 L)
- Fuel Transfer pump

### Exhaust Muffler:

- Residential grade
- Critical grade
- Hospital grade

### Available for voltages :

- 400/230V, 480/277V, 380/220V, 440/254V, 416/240V, 220/127V, 208/120V