

AQT-CU900

GENERATING SET (TECHNICAL DATA SHEET)

Standard Specifications:

1- Prime Rating:

Unlimited hours usage, with an average load factor of 80% over each 24 hour period. 10% overload is available for 1 hour in every 12 hours operation. 0 overload is permitted on standby power.

2- Standby Rating:

Limited to 500 hours annual usage, with an average load factor of 80% of the published standby power rating over each 24 hour period. Up to 300 hours of annual usage may be run continuously. No overload is permitted on standby power.

3- Engine:

Cummins, including air filters, fuel filters, oil filter, starting motor and charging alternator etc.

4- Alternator Type:

brushless AC alternator

5- Radiator:

50°C, fan protective shroud

Powered By:









"We deliver power, service and solutions in exactly the way you want."

Output Rating:

o depart racing	9.			
PRIME:		STANDBY:		
5 0 Hz—1500 Rpm	400 V, 3ph			
810 kVA	648 kW	900 kVA	720 kW	

ENGINE SPECIFICATIONS

Engine Make	CUMMINS
Engine Model	QSK23-G3
Туре	4 cycle, 6-cylinder turbocharged
Bore mm	170 mm
Stroke Model	170 mm
Displacement	23.1 litre
Flywheel Dimensions	SAE 0
Battery Charging Alternator	35 amps
Starting Voltage	24 volt, negative ground
Fuel System	Cummins direct injection HPI
Fuel Filter	Spin-on fuel filters with water separator
Lube Oil Filter and Capacity (L)	Spin on full flow filter - 103 Litres

ALTERNATOR SPECIFICATIONS

Alternator Make	Leroy Somer Stamford	
Alternator Model	HCI634H/S6L1D-D4	
Number of Poles	4	
Winding Pitch	2/3	
Insulation Class - Temp Rise	Н	
Ingress Protection Rating	IP 23	
Excitation System	Self Excited	
AVR Model	MX321	

COMPLY WITH STANDARDS

ISO 3046, BS 5514, DIN 6271, NEMA-MGI, DIN EN, BS 5000, IEC 60034,IEC 60947-2

	ALTERNATOR OPERATING DATA
Over speed	2250 rpm
Voltage Regulation	<u>+</u> 5%
Harmonic Coefficient THF	< 3.5%
Tel. influence TIF	< 50
Cooling air flow	1.42 m3/ Sec

Standard Specifications:

6- Fuel Tank:

Capacity of fuel tank is for 8-10 hours Built in fuel tank up to 800 kVA

7- Circuit Breaker:

3 pole LS MCCB

8- Control system alarms:

- Over and Under Speed
- Low and High Battery Volt.
- Start and Stop Failure
- **Over Current**
- Under / Over Generator Voltage
- Low Oil Pressure
- **Emergency stop**
- High engine temperature

9- Warranty policy:

- AQT GENERATOR products has a warranty for 12 Months or 1000 hours whichever occurs first against any manufacturing defects
- Wearing parts (filters), incorrect man made operation, maintenance failures are excluded from the warranty policy

Acoustic Enclosure Specifications:

Enclosure Type	Acoustic & Weather Proof			
Drainage Provision	Fuel and Water Drainage			
Transportation	Tested Single Point Lifting Facility & Forklift Pockets			
Ingress Protection Rating	IP 23			
Lifting	ISO Standard Lifting			
Canopy RAL Color	TAL 9010			
Base frame RAL Color	RAL 9011			
Noise Pressure level @ 7m 66db(A) @ 7mt				

Control System:

Large back-lit text display

Multiple display languages

DSENET expansion compatible

Data logging facility

Fully configurable via PC using USB communication

Front panel configuration

Efficient power save mode

3 phase generator sensing

Accumulated power monitoring (kWh, kVA h, kVA h)

Generator/load current monitoring and protection (kW)

Breaker contol via fascia buttons

Fuel and start outputs, configurable using can

4 configurable DC outputs

4 configurable analogue/digital inputs

Automatically transfers between mains (utility) and generator

Increased input and output expansion capability via dsenet

IP65 rating (with optional gasket) offers increased resistance to water ingress

Digital inputs; Analogue Inputs



DSE6110 MKII

AUTO START & AUTO MAINS FAILURE CONTROL

Dimensions:

Туре	Length (mm)	Width (mm)	Height (mm)	Fuel Tank (L)	Weight (KG)
OPEN	4300	1750	2200	1170	6300
CLOSED	6000	2440	2590	1170	9300











Engine:



COOLPAC PERFORMANCE DATA				
Cooling System Design	Air-Air Charge Cooled			
Coolant Ratio	50% ethylene gylcol; 50% water			
Coolant Capacity (L)	110			
Limiting Ambient Temp.	50.9 Degree Celsius			
Fan Power Kw	14.4			
Cooling System Air Flow (m3/s)	13.5			
Air Cleaner Type	Dry replaceable element with restriction			
	indicator			

FUEL CONS	UMPTION 1500 (50 HZ)
Fuel Consumption @ 110%	178
Fuel Consumption @ 100%	161
Fuel Consumption @ 75%	121
Fuel Consumption @ 50%	85
Fuel Consumption @ 25%	46

Optional configurations: Engine accessories: Heavy-duty air filter Coolant heater Lubricant oil heater

Fuel and Water Separator
Lube oil rotary pump

Alternator And Accessories:

ш	Leiby	SUII	161/31	IUIIII	u	
	Anti co	ond	ensati	on he	ater	
	PMG	+	AVR	\Diamond	Double	bearin
	alterna	ato	r High	volta	gel	kV

Ш	alternator High voltagek
	RTDs for Bearing and winding

Cod	oling System:
	55 degree Radiator
	Remote Radiator
Cor	ntrol System:

COII	tioi system.
	AMF
П	Parallel
й	Practical type in low temperature environment
П	Control Screen Heater
ŏ	Remote Annunciators
	Other (ComP, DEIF)
Circ	uit Breaker:

Cir	Circuit Breaker:	
Ш	3/4 poles	
	Fixed/handcart type	
	Electric mechanism	
Au	tomatic Transfer Switch (ATS):	

			-	
		ATS cabinet		
ı	7	Contractor type ATS		
ŏ	_	Motorized changeover ty	pe A	ATS

Sta	Start Battery:		
	Nickel-cadmium battery		
	Maintenance-free battery		
ă	Battery charger and selector switch		
Ğ	Charging current meter		
External Fuel Tank:			

	Charging current meter	
Exte	ernal Fuel Tank:	
	Single /double wall fuel tank Fuel Transfer pump	(500-5000 L)
Exhaust Muffler:		

LAI	LAHAUST WIGHTEN.	
	Residential grade	
	Critical grade	
	Hospital grade	
Available for voltages :		
	400/230V, 480/277V, 380/220V, 440/254V,	

416/240V,220/127V, 208/120V





Our Success

We owe our success to our hardworking, highly skilled and committed employees. Our core focus lies in providing customized integrated products and services with well-established infrastructure, equipment and manpower to support and provide the turn key solutions for various industries. We provide the latest in power generator technology equipment, allowing us to give our customers the best product and the best possible service.



Our objective is to serve customers to the utmost by providing them with the best-in-class electric generators, reliable door to door delivery, and after sales service at competitive market prices.

"We continue to build our solid reputation for excellence and response, while delivering reliable and tailored solutions to meet the customer's requirements".



At AQT Generators, we take pride in being a dynamic force in the realm of diesel generator sets, offering an extensive range of international brands renowned for their reliability and performance. Our commitment to excellence is reflected in our partnerships with world-famous engine manufacturers such as Perkins and Cummins, coupled with top-notch alternators from Stamford and Leroy Somer.





Office 409, Al Murjan, Al Nahda, Dubai, UAE

Call Us: +971 4 547 1703

Email: info@aqtgenerators.com

FOLLOW US ON OUR SOCIAL MEDIA ACCOUNTS











