

# AQT-CU625

**GENERATING SET** 

(TECHNICAL DATA SHEET)



#### 1- Prime Rating:

Unlimited hours usage, with an average load factor of 80% over each 24 hour period. 10% overload is available for 1 hour in every 12 hours operation. 0 overload is permitted on standby power.

#### 2- Standby Rating:

Limited to 500 hours annual usage, with an average load factor of 80% of the published standby power rating over each 24 hour period. Up to 300 hours of annual usage may be run continuously. No overload is permitted on standby power.

#### 3- Engine:

Cummins, including air filters, fuel filters, oil filter, starting motor and charging alternator etc.

#### 4- Alternator Type:

brushless AC alternator

#### 5- Radiator:

50°C, fan protective shroud

#### Powered By:









"We deliver power, service and solutions in exactly the way you want."

# Output Rating:

0 010 P 010 1 10101110.				
PRIME:		STANDBY:		
<b>6</b> 0 Hz—1800 Rpm	480 V, 3ph			
562.5 kVA	450 kW	625 kVA	500 kW	

# **ENGINE SPECIFICATIONS**

Engine Make	CUMMINS
Engine Model	QSZ13-G3
Туре	4 cycle, in-line, 6-cylinder turbocharged, air-cooled
Bore mm	130 mm (5.12 in.)
Stroke Model	163 mm (6.42in.)
Displacement	13 litre (793 in.3 )
Flywheel Dimensions	SAE1
Battery Charging Alternator	80 amps
Starting Voltage	24 volt, negative ground
Fuel System	HPCR
Fuel Filter	Spin-on fuel filters with water separator
Lube Oil Filter and Capacity (L)	Spin on full flow filter - 78 Litres

#### ALTERNATOR SPECIFICATIONS

Alternator Make	Leroy Somer   Stamford	
Alternator Model	HCI544C	
Number of Poles	4	
Winding Pitch	2/3	
Insulation Class - Temp Rise	Н	
Ingress Protection Rating	IP 23	
Excitation System	Self Excited	
AVR Model	SX440	

### **COMPLY WITH STANDARDS**

ISO 3046, BS 5514, DIN 6271, NEMA-MGI, DIN EN, BS 5000, IEC 60034,IEC 60947-2

	ALTERNATOR OPERATING DATA
Over speed	2250 rpm
Voltage Regulation	<u>+</u> 1%
Harmonic Coefficient THF	< 3.5%
Tel. influence TIF	< 50
Cooling air flow	1.035m3/ Sec

# **Standard Specifications:**

#### 6- Fuel Tank:

Capacity of fuel tank is for 8-10 hours Built in fuel tank up to 800 kVA

#### 7- Circuit Breaker:

3 pole LS MCCB

#### 8- Control system alarms:

- Over and Under Speed
- Low and High Battery Volt.
- Start and Stop Failure
- **Over Current**
- Under / Over Generator Voltage
- Low Oil Pressure
- **Emergency stop**
- High engine temperature

#### 9- Warranty policy:

- AQT GENERATOR products has a warranty for 12 Months or 1000 hours whichever occurs first against any manufacturing defects
- Wearing parts (filters), incorrect man made operation, maintenance failures are excluded from the warranty policy

#### **Acoustic Enclosure Specifications:**

Enclosure Type	Acoustic & Weather Proof	
Drainage Provision	Fuel and Water Drainage	
Transportation	Tested Single Point Lifting Facility & Forklift Pockets	
Ingress Protection Rating	IP 23	
Lifting	ISO Standard Lifting	
Canopy RAL Color	TAL 9010	
Base frame RAL Color	RAL 9011	
Noise Pressure level @ 7m 66db(A) @ 7mt		

# **Control System:**

Large back-lit text display

Multiple display languages

**DSENET** expansion compatible

Data logging facility

Fully configurable via PC using USB communication

Front panel configuration

Efficient power save mode

3 phase generator sensing

Accumulated power monitoring (kWh, kVA h, kVA h)

Generator/load current monitoring and protection (kW)

Breaker contol via fascia buttons

Fuel and start outputs, configurable using can

4 configurable DC outputs

4 configurable analogue/digital inputs

Automatically transfers between mains (utility) and generator

Increased input and output expansion capability via dsenet

IP65 rating (with optional gasket) offers increased resistance to water ingress

Digital inputs; Analogue Inputs



# DSE6110 MKII

**AUTO START & AUTO MAINS** FAILURE CONTROL

# **Dimensions:**

Туре	Length (mm)	Width (mm)	Height (mm)	Fuel Tank (L)	Weight (KG)
OPEN	3800	1200	1800	1110	3760
CLOSED	4920	1600	2210	1110	5160













# Engine:



COOLPAC PERFORMANCE DATA		
Cooling System Design	Air-Air Charge Cooled	
Coolant Ratio	50% ethylene gylcol; 50% water	
Coolant Capacity (L)	62	
Limiting Ambient Temp.	50 Degree Celsius	
Fan Power Kw	18.5	
Cooling System Air Flow (m3/s)	8.1	
Air Cleaner Type	Normal duty dry replaceable element with	
	restriction indicator	

FUEL CONSUMPTION 1800 (60 HZ)		
Fuel Consumption @ 110%	118.6	
Fuel Consumption @ 100%	104.1	
Fuel Consumption @ 75%	75.7	
Fuel Consumption @ 50%	50.8	
Fuel Consumption @ 25%	28.0	

#### Optional configurations: **Engine accessories:** Heavy-duty air filter Coolant heater Lubricant oil heater Fuel and Water Separator Lube oil rotary pump **Alternator And Accessories:** Leroy somer/stamford Anti condensation heater PMG + AVR $\diamondsuit$ Double bearing alternator High voltage \_\_\_\_kV RTDs for Bearing and winding **Cooling System:** 55 degree Radiator Remote Radiator **Control System:** AMF Parallel Practical type in low temperature environment Control Screen Heater **Remote Annunciators** Other (ComP, DEIF) Circuit Breaker: 3/4 poles Fixed/handcart type Electric mechanism **Automatic Transfer Switch (ATS):** ☐ ATS cabinet Contractor type ATS Motorized changeover type ATS **Start Battery:**

#### **Exhaust Muffler:**

**External Fuel Tank:** 

Residential grade Critical grade

Hospital grade

Available for voltages :

Nickel-cadmium battery Maintenance-free battery Battery charger and selector switch

Charging current meter

Fuel Transfer pump

400/230V, 480/277V, 380/220V, 440/254V, 416/240V,220/127V, 208/120V

Single /double wall fuel tank (500-5000 L)







#### **Our Success**

We owe our success to our hardworking, highly skilled and committed employees. Our core focus lies in providing customized integrated products and services with well-established infrastructure, equipment and manpower to support and provide the turn key solutions for various industries. We provide the latest in power generator technology equipment, allowing us to give our customers the best product and the best possible service.

#### **Objectives**

Our objective is to serve customers to the utmost by providing them with the best-in-class electric generators, reliable door to door delivery, and after sales service at competitive market prices.

"We continue to build our solid reputation for excellence and response, while delivering reliable and tailored solutions to meet the customer's requirements".



At AQT Generators, we take pride in being a dynamic force in the realm of diesel generator sets, offering an extensive range of international brands renowned for their reliability and performance. Our commitment to excellence is reflected in our partnerships with world-famous engine manufacturers such as Perkins and Cummins, coupled with top-notch alternators from Stamford and Leroy Somer.





Office 409, Al Murjan, Al Nahda, Dubai, UAE

Call Us: +971 4 547 1703

Email: info@aqtgenerators.com

# **FOLLOW US ON OUR SOCIAL MEDIA ACCOUNTS**











