

AQT-CU234

GENERATING SET

(TECHNICAL DATA SHEET)



1- Prime Rating:

Unlimited hours usage, with an average load factor of 80% over each 24 hour period. 10% overload is available for 1 hour in every 12 hours operation. 0 overload is permitted on standby power.

2- Standby Rating:

Limited to 500 hours annual usage, with an average load factor of 80% of the published standby power rating over each 24 hour period. Up to 300 hours of annual usage may be run continuously. No overload is permitted on standby power.

3- Engine:

Cummins, including air filters, fuel filters, oil filter, starting motor and charging alternator etc.

4- Alternator Type:

brushless AC alternator

5- Radiator:

50°C, fan protective shroud

Powered By:









"We deliver power, service and solutions in exactly the way you want."

Outnut Rating.

output maning.			
PRIME:		STANDBY:	
6 0 Hz—1800 Rpm	480 V, 3ph		
212.5 kVA	170 kW	234 kVA	187 kW

ENGINE SPECIFICATIONS	
Engine Make	CUMMINS
Engine Model	6CTA8.3-G2
Туре	In-line, 6-Cylinder Diesel, Turbocharged & Aftercooled
Bore mm	114 mm
Stroke Model	135 mm
Displacement	8.3 L
Flywheel Dimensions	3/11.5
Battery Charging Alternator	37 amps
Starting Voltage	12 volt
Fuel System	BYC PB/RSV Mechanical
Fuel Filter	Spin on fuel filters
Lube Oil Filter and Capacity (L)	Spin on full flow filter - 27.6 Litres

Leroy Somer Stamford
UCI274H
4
2/3
Н
IP 23
SHUNT
SX460 AS440

COMPLY WITH STANDARDS

ISO 3046, BS 5514, DIN 6271, NEMA-MGI, DIN EN, BS 5000, IEC 60034,IEC 60947-2

ALTERNATOR OPERATING DATA		
Over speed	2250 rpm	
Voltage Regulation	<u>+</u> 1%	
Harmonic Coefficient THF	< 3.5%	
Tel. influence TIF	< 50	
Cooling air flow	0.48 m3/ Sec	

Standard Specifications:

6- Fuel Tank:

Capacity of fuel tank is for 8-10 hours Built in fuel tank up to 800 kVA

7- Circuit Breaker:

3 pole LS MCCB

8- Control system alarms:

- Over and Under Speed
- Low and High Battery Volt.
- Start and Stop Failure
- **Over Current**
- Under / Over Generator Voltage
- Low Oil Pressure
- **Emergency stop**
- High engine temperature

9- Warranty policy:

- AQT GENERATOR products has a warranty for 12 Months or 1000 hours whichever occurs first against any manufacturing defects
- Wearing parts (filters), incorrect man made operation, maintenance failures are excluded from the warranty policy

Acoustic Enclosure Specifications:

Enclosure Type	Acoustic & Weather Proof
Drainage Provision	Fuel and Water Drainage
Transportation	Tested Single Point Lifting Facility & Forklift Pockets
Ingress Protection Rating	IP 23
Lifting	ISO Standard Lifting
Canopy RAL Color	TAL 9010
Base frame RAL Color	RAL 9011
Noise Pressure level @ 7n	n 66db(A) @ 7mt

Control System:

Large back-lit text display

Multiple display languages

DSENET expansion compatible

Data logging facility

Fully configurable via PC using USB communication

Front panel configuration

Efficient power save mode

3 phase generator sensing

Accumulated power monitoring (kWh, kVA h, kVA h)

Generator/load current monitoring and protection (kW)

Breaker contol via fascia buttons

Fuel and start outputs, configurable using can

4 configurable DC outputs

4 configurable analogue/digital inputs

Automatically transfers between mains (utility) and generator

Increased input and output expansion capability via dsenet

IP65 rating (with optional gasket) offers increased resistance to water ingress

Digital inputs; Analogue Inputs



DSE6110 MKII

AUTO START & AUTO MAINS FAILURE CONTROL

Dimensions:

Туре	Length (mm)	Width (mm)	Height (mm)	Fuel Tank (L)	Weight (KG)
OPEN	2248	900	1560	400	1560
CLOSED	3562	1155	1832	400	2201











Engine:



COOLPAC PERFORMANCE DATA		
Cooling System Design	Jacket Water cooled	
Coolant Ratio	50% ethylene gylcol; 50% water	
Coolant Capacity (L)	10.2	
Limiting Ambient Temp.	17 Degree Celsius	
Fan Power Kw	2.7	
Cooling System Air Flow (m3/s)	0.48	
Air Cleaner Type	Dry replaceable element with restriction	
	indicator	

FUEL CONSUMPTION 1800 (60 HZ)	
Fuel Consumption @ 110%	49
Fuel Consumption @ 100%	44
Fuel Consumption @ 75%	33
Fuel Consumption @ 50%	23
Fuel Consumption @ 25%	14

Optional configurations:

•	O .
Engi	ine accessories:
]	Heavy-duty air filter
	Coolant heater
]	Lubricant oil heater
]]	Fuel and Water Separator
]	Lube oil rotary pump
J	Lube on rotary pump
Alte	rnator And Accessories:
	Leroy somer/stamford
	Anti condensation heater
	PMG + AVR \diamondsuit Double bearing
	alternator High voltagekV
	RTDs for Bearing and winding
Coo	ling System:
7	55 degree Radiator
1	Remote Radiator
J	Nemote Natiator
	trol System:
	AMF
٦	Parallel
i	Practical type in low temperature environment
- -	Control Screen Heater
i	Remote Annunciators
	Other (ComP, DEIF)
Circ	uit Breaker:
	3/4 poles
٦	Fixed/handcart type
5	Electric mechanism
_	Liectric mechanism
_	omatic Transfer Switch (ATS):
╛	ATS cabinet
	Contractor type ATS
]	Motorized changeover type ATS
Star	t Battery:
7	
_	Nickel-cadmium battery
	Maintenance-free battery
	Battery charger and selector switch
	Charging current meter
Exte	rnal Fuel Tank:
	Single /double wall fuel tank (500-5000 L)
	Fuel Transfer pump
Fyh	aust Muffler:
7	Residential grade
i	Critical grade
i	
	Hospital grade
Ava	ilable for voltages :

400/230V, 480/277V, 380/220V, 440/254V,

416/240V,220/127V, 208/120V







Our Success

We owe our success to our hardworking, highly skilled and committed employees. Our core focus lies in providing customized integrated products and services with well-established infrastructure, equipment and manpower to support and provide the turn key solutions for various industries. We provide the latest in power generator technology equipment, allowing us to give our customers the best product and the best possible service.

Objectives

Our objective is to serve customers to the utmost by providing them with the best-in-class electric generators, reliable door to door delivery, and after sales service at competitive market prices.

"We continue to build our solid reputation for excellence and response, while delivering reliable and tailored solutions to meet the customer's requirements".



At AQT Generators, we take pride in being a dynamic force in the realm of diesel generator sets, offering an extensive range of international brands renowned for their reliability and performance. Our commitment to excellence is reflected in our partnerships with world-famous engine manufacturers such as Perkins and Cummins, coupled with top-notch alternators from Stamford and Leroy Somer.





Office 409, Al Murjan, Al Nahda, Dubai, UAE

Call Us: +971 4 547 1703

Email: info@aqtgenerators.com

FOLLOW US ON OUR SOCIAL MEDIA ACCOUNTS











