

# AQT-150

## GENERATING SET (TECHNICAL DATA SHEET)



*"We deliver power, service and solutions in exactly the way you want."*

### Standard Specifications:

#### 1- Prime Rating:

Unlimited hours usage, with an average load factor of 80% over each 24 hour period. 10% overload is available for 1 hour in every 12 hours operation. 0 overload is permitted on standby power.

#### 2- Standby Rating:

Limited to 500 hours annual usage, with an average load factor of 80% of the published standby power rating over each 24 hour period. Up to 300 hours of annual usage may be run continuously. No overload is permitted on standby power.

#### 3- Engine:

Perkins, including air filters, fuel filters, oil filter, starting motor and charging alternator etc.

#### 4- Alternator Type:

brushless AC alternator

#### 5- Radiator:

50°C, fan protective shroud

### Output Rating:

PRIME:		STANDBY:	
50 Hz—1500 Rpm 400 V, 3ph			
135 kVA	108 kW	150 kVA	120 kW
60 Hz—1800 Rpm 480 V, 3ph			
152kVA	122 kW	169kVA	135kW

### ENGINE SPECIFICATIONS

Engine Make	PERKINS
Engine Model	1106A-70TAG1
No. of Cylinders	6 vertical in-line
Cycle	4 Stroke
Aspiration	Turbocharged
Cooling Method	Water cooled
Governing Type	Electronic
Governing Class	G2 - ISO 8528 Part 1
Compression Ratio	18.2:1
Displacement	7.01 L
Bore/Stroke	105 x 135 mm
Dynamic Charging Alternator	55AMP, 12V

### ALTERNATOR SPECIFICATIONS

Alternator Make	Leroy Somer   STAMFORD
Alternator Model	TAL-044-H   UCI274E
Number of Poles	4
Number of Winding Leads	6
Type of Bearing	Single Bearing
Insulation Class - Temp Rise	Cont. H - 125/40 °C
Ingress Protection Rating	IP 23
Excitation System	Self Excited
AVR Model	R120

### Comply with Standards

ISO 3046, BS 5514, DIN 6271, NEMA-MGI, DIN EN, BS 5000, IEC 60034, IEC 60947-2

### Powered By:



Diesel Generator



LEROY-SOMER



### Alternator Operating data

Over speed	2250 rpm
Voltage Regulation	+ 1%
Harmonic Coefficient THF	< 2%
Tel. influence TIF	< 50
Cooling air flow	0.25 m <sup>3</sup> / Sec



## Standard Specifications:

### 6- Fuel Tank:

Capacity of fuel tank is for 8 –10 hours running  
Built in fuel tank up to 800 kVA

### 7- Circuit Breaker:

3 pole LS MCCB

### 8- Control system alarms:

- Over and Under Speed
- Low and High Battery Volt.
- Start and Stop Failure
- Over Current
- Under / Over Generator Voltage
- Low Oil Pressure
- Emergency stop
- High engine temperature

### 9- Warranty policy:

- **AQT GENERATOR** products has a warranty for 12 Months or 1000 hours whichever occurs first against any manufacturing defects
- Wearing parts (filters), incorrect man made operation, maintenance failures are excluded from the warranty policy

## Acoustic Enclosure Specifications:

Enclosure Type	Acoustic & Weather Proof
Drainage Provision	Fuel and Water Drainage
Transportation	Tested Single Point Lifting Facility & Forklift Pockets
Ingress Protection Rating	IP 23
Lifting	ISO Standard Lifting
Canopy RAL Color	TAL 9010
Base frame RAL Color	RAL 9011
Noise Pressure level @ 7m 70db(A) @ 7mt	

## Control System:

Large back-lit text display	Generator/load current monitoring and protection (kW)
Multiple display languages	Breaker control via fascia buttons
DSENET expansion compatible	Fuel and start outputs, configurable using can
Data logging facility	4 configurable DC outputs
Fully configurable via PC using USB communication	4 configurable analogue/digital inputs
Front panel configuration	Automatically transfers between mains (utility) and generator
Efficient power save mode	Increased input and output expansion capability via dsenet
3 phase generator sensing	IP65 rating (with optional gasket) offers increased resistance to water ingress
Accumulated power monitoring (kWh, kVA h, kVAR h)	Digital inputs; Analogue Inputs



### DSE4520 MKII

AUTO START & AUTO MAINS  
FAILURE CONTROL

## Dimensions:

Type	Length (mm)	Width (mm)	Height (mm)	Fuel Tank (L)	Weight (KG)
OPEN	2500	775	1425	280	1325
CLOSED	3200	1100	1790	280	1975



+971 4 547 1703



info@aqtgenerators.com



http://www.aqtgenerators.com



## Engine:



Perkins heavy duty high performance industrial type diesel engine.

### COOLING SYSTEM

Total Coolant Capacity (L) 21 L

Cooling Fan Air Flow 182 m<sup>3</sup>/ min

Radiator Fan Load 4.4 kW

Heat Radiation to Room (PRP) 12.5 kW

Heat Radiation to Room (ESP) 15.3 kW

### LUBRICATION SYSTEM

Oil Filter Type Spin-On Full Flow

Total Oil Capacity 16.5 L

Oil Type API-CH-4 or ACEA E5

### EXHAUST SYSTEM

Muffler Type Industrial Grade

Max. Back Pressure 6 kPa

Exhaust Gas Flow (PRP/ESP) 20.75 /22.6 m<sup>3</sup>/ min

Exhaust Gas Temperature < 5760C

### FUEL SYSTEM

Recommended Fuel Class A2 Diesel

Fuel Consumption Standby 33.8 L/hr

Fuel Consumption 100% PRP 30.2 L/hr

Fuel Consumption 75% PRP 22.7 L/hr

Fuel Consumption 50% PRP 15.9 L/hr

### AIR SYSTEM

Air Filter Type Dry Element

Combustion Air Flow (PRP) 7.64 m<sup>3</sup>/min

Combustion Air Flow (ESP) 8.09 m<sup>3</sup>/min

Max Air Filter Intake Restriction 5 kPa

## Optional configurations:

### Engine accessories:

- Heavy-duty air filter
- Coolant heater
- Lubricant oil heater
- Fuel and Water Separator
- Lube oil rotary pump

### Alternator And Accessories:

- Leroy somer/stamford
- Anti condensation heater
- PMG + AVR  Double bearing
- alternator High voltage \_\_\_\_\_kV
- RTDs for Bearing and winding

### Cooling System:

- 55 degree Radiator
- Remote Radiator

### Control System:

- AMF
- Parallel
- Practical type in low temperature environment
- Control Screen Heater
- Remote Annunciators
- Other (ComP, DEIF)

### Circuit Breaker:

- 3/4 poles
- Fixed/handcart type
- Electric mechanism

### Automatic Transfer Switch (ATS):

- ATS cabinet
- Contractor type ATS
- Motorized changeover type ATS

### Start Battery:

- Nickel-cadmium battery
- Maintenance-free battery
- Battery charger and selector switch
- Charging current meter

### External Fuel Tank:

- Single /double wall fuel tank (500-5000 L)
- Fuel Transfer pump

### Exhaust Muffler:

- Residential grade
- Critical grade
- Hospital grade

### Available for voltages :

- 400/230V, 480/277V, 380/220V, 440/254V, 416/240V, 220/127V, 208/120V

## Our Success

We owe our success to our hardworking, highly skilled and committed employees. Our core focus lies in providing customized integrated products and services with well-established infrastructure, equipment and manpower to support and provide the turn key solutions for various industries. We provide the latest in power generator technology equipment, allowing us to give our customers the best product and the best possible service.

## Objectives

Our objective is to serve customers to the utmost by providing them with the best-in-class electric generators, reliable door to door delivery, and after sales service at competitive market prices.

**“We continue to build our solid reputation for excellence and response, while delivering reliable and tailored solutions to meet the customer's requirements”.**



# AQT GENERATORS

*At AQT Generators, we take pride in being a dynamic force in the realm of diesel generator sets, offering an extensive range of international brands renowned for their reliability and performance. Our commitment to excellence is reflected in our partnerships with world-famous engine manufacturers such as Perkins and Cummins, coupled with top-notch alternators from Stamford and Leroy Somer.*



القوة الذكية للتجارة ش.ذ.م.م  
ALOWA ALTHAKYA TRADING L.L.C

**AQT GENERATORS**

## CONTACT US

Office 409, Al Murjan, Al Nahda,  
Dubai, UAE


Call Us: +971 4 547 1703

Email: [info@aqtgenerators.com](mailto:info@aqtgenerators.com)

## FOLLOW US ON OUR SOCIAL MEDIA ACCOUNTS




WhatsApp



LinkedIn



Facebook



Instagram



TikTok



Youtube