


AQT-2000

GENERATING SET
(TECHNICAL DATA SHEET)



"We deliver power, service and solutions in exactly the way you want."

Standard Specifications:

1- Prime Rating:

Unlimited hours usage, with an average load factor of 80% over each 24 hour period. 10% overload is available for 1 hour in every 12 hours operation. 0 overload is permitted on standby power.

2- Standby Rating:

Limited to 500 hours annual usage, with an average load factor of 80% of the published standby power rating over each 24 hour period. Up to 300 hours of annual usage may be run continuously. No overload is permitted on standby power.

3- Engine:

Perkins, including air filters, fuel filters, oil filter, starting motor and charging alternator etc.

4- Alternator Type:

brushless AC alternator

5- Radiator:

50°C, fan protective shroud

Output Rating:

PRIME:		STANDBY:	
50 Hz—1500 Rpm	400 V, 3ph		
1844 kVA	1476 kW	2028 kVA	1622 kW
60 Hz—1800 Rpm	480 V, 3ph		
N/A	N/A	N/A	N/A

ENGINE SPECIFICATIONS

Engine Make	PERKINS
Engine Model	4016TAG1A
No. of Cylinders	16 60° Vee form
Cycle	4 Stroke
Aspiration	Turbocharged & air to air charged cooled
Cooling Method	Water cooled
Governing Type	Electronic
Governing Class	G2 - ISO 8528 Part 1
Compression Ratio	13.6:1
Displacement	61.123 litres
Bore/Stroke	160 x 190 mm
Dynamic Charging Alternator	55 AMP, 24V

ALTERNATOR SPECIFICATIONS

Alternator Make	Leroy Somer STAMFORD
Alternator Model	LSA52.3 S5 PI734E
Number of Poles	4
Number of Winding Leads	12
Type of Bearing	Single Bearing
Insulation Class - Temp Rise	Cont. H - 125/40 °C
Ingress Protection Rating	IP 23
Excitation System	AREP + PMI
AVR Model	D 510C

Comply with Standards

ISO 3046, BS 5514, DIN 6271, NEMA-MGI, DIN EN, BS 5000, IEC 60034, IEC 60947-2

Alternator Operating data

Over speed	2250 rpm
Voltage Regulation	+ 0.5%
Harmonic Coefficient THF	< 2%
Tel. influence TIF	< 50
Cooling air flow	2.5 m ³ / Sec

Powered By:



Diesel Generator



LEROY-SOMER

meccalte



Standard Specifications:

6- Circuit Breaker:

3 pole LS MCCB

7- Control system alarms:

- Over and Under Speed
- Low and High Battery Volt.
- Start and Stop Failure
- Over Current
- Under / Over Generator Voltage
- Low Oil Pressure
- Emergency stop
- High engine temperature

8- Warranty policy:

- **AQT GENERATOR** products has a warranty for 12 Months or 1000 hours whichever occurs first against any manufacturing defects
- Wearing parts (filters), incorrect man made operation, maintenance failures are excluded from the warranty policy

Acoustic Enclosure Specifications:

Enclosure Type	Acoustic & Weather Proof
Drainage Provision	Fuel and Water Drainage
Transportation	Tested Single Point Lifting Facility & Forklift Pockets
Ingress Protection Rating	IP 23
Lifting	ISO Standard Lifting
Canopy RAL Color	TAL 9010
Base frame RAL Color	RAL 9011
Noise Pressure level @ 7m TBD	

Control System:

Large back-lit text display

Multiple display languages

DSENET expansion compatible

Data logging facility

Fully configurable via PC using USB communication

Front panel configuration

Efficient power save mode

3 phase generator sensing

Accumulated power monitoring (kWh, kVA h, kVAh)

Generator/load current monitoring and protection (kW)

Breaker control via fascia buttons

Fuel and start outputs, configurable using can

4 configurable DC outputs

4 configurable analogue/digital inputs

Automatically transfers between mains (utility) and generator

Increased input and output expansion capability via dsenet

IP65 rating (with optional gasket) offers increased resistance to water ingress

Digital inputs; Analogue Inputs



DSE6110 MKII

AUTO START & AUTO MAINS
FAILURE CONTROL

Dimensions:

Type	Length (mm)	Width (mm)	Height (mm)	Fuel Tank (L)	Weight (KG)
OPEN	6000	2750	3600	NA*	15400
CLOSED	12192	2438	2896	NA*	26500



+971 4 547 1703



info@aqtgenerators.com



http://www.aqtgenerators.com



Engine:



Perkins heavy duty high performance industrial type diesel engine.

COOLING SYSTEM

Total Coolant Capacity (L) 210 L

Cooling Fan Air Flow 2394 m³/ min

Radiator Fan Load 51 kW

Heat Radiation to Room (PRP) 103 Kw

Heat Radiation to Room (ESP) 107 kW

LUBRICATION SYSTEM

Oil Filter Type Spin-On Full Flow

Total Oil Capacity 214 L

Oil Type API-CH-4 or ACEA E5

EXHAUST SYSTEM

Muffler Type Industrial Grade

Max. Back Pressure 3.0 kPa

Exhaust Gas Flow (PRP/ESP) 343 m³/ min

3

Exhaust Gas Temperature $\leq 439^{\circ}\text{C}$

FUEL SYSTEM

Recommended Fuel Class A2 Diesel

Fuel Consumption Standby 424 L/hr

Fuel Consumption 100% PRP 383 L/hr

Fuel Consumption 75% PRP 277 L/hr

Fuel Consumption 50% PRP 155 L/hr

AIR SYSTEM

Air Filter Type Cylindrical paper pleat

Combustion Air Flow (PRP) 132 m³/min

Combustion Air Flow (ESP) 140 m³/min

Max Air Filter Intake Restriction 3.7 kPa

Optional configurations:

Engine accessories:

- Heavy-duty air filter
- Coolant heater
- Lubricant oil heater
- Fuel and Water Separator
- Lube oil rotary pump

Alternator And Accessories:

- Leroy somer/stamford
- Anti condensation heater
- PMG + AVR \diamond Double bearing
- Alternator High voltage _____kV
- RTDs for Bearing and winding

Cooling System:

- 55 degree Radiator
- Remote Radiator

Control System:

- AMF
- Parallel
- Practical type in low temperature environment
- Control Screen Heater
- Remote Annunciators
- Other (Comp, DEIF)

Circuit Breaker:

- 3/4 poles
- Fixed/handcart type
- Electric mechanism

Automatic Transfer Switch (ATS):

- ATS cabinet
- Contractor type ATS
- Motorized changeover type ATS

Start Battery:

- Nickel-cadmium battery
- Maintenance-free battery
- Battery charger and selector switch
- Charging current meter

External Fuel Tank:

- Single /double wall fuel tank (500-5000 L)
- Fuel Transfer pump

Exhaust Muffler:

- Residential grade
- Critical grade
- Hospital grade

Available for voltages :

- 400/230V, 480/277V, 380/220V, 440/254V, 416/240V, 220/127V, 208/120V

Our Success

We owe our success to our hardworking, highly skilled and committed employees. Our core focus lies in providing customized integrated products and services with well-established infrastructure, equipment and manpower to support and provide the turn key solutions for various industries. We provide the latest in power generator technology equipment, allowing us to give our customers the best product and the best possible service.

Objectives

Our objective is to serve customers to the utmost by providing them with the best-in-class electric generators, reliable door to door delivery, and after sales service at competitive market prices.

“We continue to build our solid reputation for excellence and response, while delivering reliable and tailored solutions to meet the customer's requirements”.



AQT GENERATORS

At AQT Generators, we take pride in being a dynamic force in the realm of diesel generator sets, offering an extensive range of international brands renowned for their reliability and performance. Our commitment to excellence is reflected in our partnerships with world-famous engine manufacturers such as Perkins and Cummins, coupled with top-notch alternators from Stamford and Leroy Somer.



القوة الذكية للتجارة ش.ذ.م.م
ALOWA ALTHAKYA TRADING L.L.C

AQT GENERATORS

CONTACT US

Office 409, Al Murjan, Al Nahda,
Dubai, UAE


Call Us: +971 4 547 1703

Email: info@aqtgenerators.com

FOLLOW US ON OUR SOCIAL MEDIA ACCOUNTS




WhatsApp



LinkedIn



Facebook



Instagram



TikTok



Youtube