

AQT-CU150 GENERATING SET (TECHNICAL DATA SHEET)

Standard Specifications:

1- Prime Rating:

Unlimited hours usage, with an average load factor of 80% over each 24 hour period. 10% overload is available for 1 hour in every 12 hours operation. 0 overload is permitted on standby power.

2- Standby Rating:

Limited to 500 hours annual usage, with an average load factor of 80% of the published standby power rating over each 24 hour period. Up to 300 hours of annual usage may be run continuously. No overload is permitted on standby power.

3- Engine:

Cummins, including air filters, fuel filters, oil filter, starting motor and charging alternator etc.

4- Alternator Type: brushless AC alternator

5- Radiator: 50°C, fan protective shroud

Powered By:







"We deliver power, service and solutions in exactly the way you want."

Output Rating:

PRIME:		STANDBY:		
50 Hz—1500 Rpm	400 V, 3ph			
135 kVA	108 kW	150 kVA	120 kW	

ENGINE SPECIFICATIONS	
Engine Make	CUMMINS
Engine Model	6BTAA5.9-G2
Туре	In-line, 6-Cylinder Diesel, Turbocharged & Charged Air Cooled
Bore mm	102 mm
Stroke Model	120 mm
Displacement	5.9 L
Flywheel Dimensions	3/11.5
Battery Charging Alternator	37 amps
Starting Voltage	12 volt
Fuel System	BYC PB/GAC 24 V
Fuel Filter	Spin on fuel filters
Lube Oil Filter and Capacity (L)	Spin on full flow filter - 14.2 Litres
ALTERNATOR SPECIFICATIONS	

Alternator Make	Leroy Somer 1 Stamford
Alternator Model	TAL-044-J I UCI274E
Number of Poles	4
Winding Pitch	2/3
Insulation Class - Temp Rise	н
Ingress Protection Rating	IP 23
Excitation System	Self Excited
AVR Model	MX341

COMPLY WITH STANDARDS

ISO 3046, BS 5514, DIN 6271, NEMA-MGI, DIN EN, BS 5000, IEC 60034, IEC 60947-2

ALTERNATOR OPERATING DATA		
Over speed	2250 rpm	
Voltage Regulation	<u>+</u> 1%	
Harmonic Coefficient THF	< 3.5%	
Tel. influence TIF	< 50	
Cooling air flow	0.617 m3/ Sec	



Standard Specifications:

6- Fuel Tank:

Capacity of fuel tank is for 8-10 hours running Built in fuel tank up to 800 kVA

7- Circuit Breaker:

LS

8- Control system alarms:

- Over and Under Speed
- Low and High Battery Volt.
- Start and Stop Failure
- Over Current
- Under / Over Generator Voltage
- Low Oil Pressure
- Emergency stop
- High engine temperature

9- Warranty policy:

- AQT GENERATOR products has a warranty for 12 Months or 1000 hours whichever occurs first against any manufacturing defects
- Wearing parts (filters), incorrect man made operation, maintenance failures are excluded from the warranty policy

Acoustic Enclosure Specifications:

Enclosure Type	Acoustic & Weather Proof	
Drainage Provision	Fuel and Water Drainage	
Transportation	Tested Single Point Lifting Facility & Forklift Pockets	
Ingress Protection Rating	IP 23	
Lifting	ISO Standard Lifting	
Canopy RAL Color	TAL 9010	
Base frame RAL Color	RAL 9011	
Noise Pressure level @ 7m 66db(A) @ 7mt		

Control System:

- Large back-lit text display
- Multiple display languages
- DSENET expansion compatible
- Data logging facility
- Fully configurable via PC using USB communication
- Front panel configuration
- Efficient power save mode
- 3 phase generator sensing

Accumulated power monitoring (kWh, kVA h, kVA h)



Dimensions:

Length Width Height Fuel Tank Weight Type (mm) (mm) (mm) (L) (KG) 400 OPEN 2500 775 1425 1325 1100 1790 400 CLOSED 3200 1975



OT GENERATOR



Generator/load current monitoring and protection (kW)

- 4 configurable DC outputs
- 4 configurable analogue/digital inputs
- Automatically transfers between mains (utility) and generator
- Increased input and output expansion capability via dsenet IP65 rating (with optional gasket) offers increased resistance to water ingress
- Digital inputs; Analogue Inputs

DSE 4520

AUTO START & AUTO MAINS FAILURE CONTROL



Engine:



COOLPAC PERFORMANCE DATA

Cooling System Design	Jacket Water cooled
Coolant Ratio	50% ethylene gylcol; 50% water
Coolant Capacity (L)	10
Limiting Ambient Temp.	50 Degree Celsius
Fan Power Kw	2.7
Cooling System Air Flow (m3/s)	0.25
Air Cleaner Type	Dry replaceable element with restriction
	indicator

FUEL CONSUMPTION 1500 (50 HZ)		
Fuel Consumption @ 110%	34	
Fuel Consumption @ 100%	30	
Fuel Consumption @ 75%	23	
Fuel Consumption @ 50%	16	
Fuel Consumption @ 25%	9	

Optional configurations:

Engine accessories:

- Heavy-duty air filter
- Coolant heater Lubricant oil heater
- Fuel and Water Separator
- Lube oil rotary pump

Alternator And Accessories:

- Leroy somer/stamford
- Anti condensation heater
- PMG + AVR 🛇 Double bearing
- alternator High voltage _____kV
- RTDs for Bearing and winding

Cooling System:

- 55 degree Radiator
- Remote Radiator Π

Control System:

- AMF
- Parallel
- Practical type in low temperature environment
 - Control Screen Heater
- Remote Annunciators
- Other (ComP, DEIF)

Circuit Breaker:

- 3/4 poles
- Fixed/handcart type П
- Electric mechanism

Automatic Transfer Switch (ATS):

- ATS cabinet
- Contractor type ATS
- Motorized changeover type ATS

Start Battery:

- Nickel-cadmium battery
- Maintenance-free battery
- Battery charger and selector switch
- Charging current meter

External Fuel Tank:

- Single /double wall fuel tank (500-5000 L)
- Fuel Transfer pump

Exhaust Muffler:

- Residential grade
- Critical grade
- Hospital grade

Available for voltages :

400/230V, 480/277V, 380/220V, 440/254V, 416/240V,220/127V, 208/120V



Our Success

We owe our success to our hardworking, highly skilled and committed employees. Our core focus lies in providing customized integrated products and services with well-established infrastructure, equipment and manpower to support and provide the turn key solutions for various industries. We provide the latest in power generator technology equipment, allowing us to give our customers the best product and the best possible service.

Objectives

Our objective is to serve customers to the utmost by providing them with the best-in-class electric generators, reliable door to door delivery, and after sales service at competitive market prices.

"We continue to build our solid reputation for excellence and response, while delivering reliable and tailored solutions to meet the customer's requirements".



At AQT Generators, we take pride in being a dynamic force in the realm of diesel generator sets, offering an extensive range of international brands renowned for their reliability and performance. Our commitment to excellence is reflected in our partnerships with world-famous engine manufacturers such as Perkins and Cummins, coupled with top-notch alternators from Stamford and Leroy Somer.





Office 204, Al Owais Building, Port Saeed, Plot No. 388-0, Dubai, UAE Call Us: +971 4 547 1703 Email: info@aqtgenerators.com

FOLLOW US ON OUR SOCIAL MEDIA ACCOUNTS

