

# AQT-CU320

**GENERATING SET** 

(TECHNICAL DATA SHEET)



#### 1- Prime Rating:

Unlimited hours usage, with an average load factor of 80% over each 24 hour period. 10% overload is available for 1 hour in every 12 hours operation. 0 overload is permitted on standby power.

#### 2- Standby Rating:

Limited to 500 hours annual usage, with an average load factor of 80% of the published standby power rating over each 24 hour period. Up to 300 hours of annual usage may be run continuously. No overload is permitted on standby power.

#### 3- Engine:

Cummins, including air filters, fuel filters, oil filter, starting motor and charging alternator etc.

4- Alternator Type:

brushless AC alternator

5- Radiator:

50°C, fan protective shroud

#### Powered By:









"We deliver power, service and solutions in exactly the way you want."

Output Rating:

o dep de Hading.				
PRIME:		STANDBY:		
<b>6</b> 0 Hz—1800 Rpm 480 V, 3ph				
295 kVA	236 kW	320 kVA	256 kW	

ENGINE SPECIFICATIONS	
Engine Make	CUMMINS
Engine Model	6LTAA9.5-G3
Туре	4 cycle, in-line, Turbo Charged, Air-cooled, 6-cylinder
Bore mm	116 mm (4.58 in.)
Stroke Model	148 mm (5.82 in.)
Displacement	9.5 litre
Flywheel Dimensions	SAE1
Battery Charging Alternator	70 amps
Starting Voltage	24 volt, negative ground
Fuel System	Bosch direct injection
Fuel Filter	Spin on fuel filters with Water Separator
Lube Oil Filter and Capacity (L)	Spin on full flow filter - 32.4 Litres

ALTERNATOR SPECIFICATIONS	
Alternator Make	Leroy Somer   Stamford
Alternator Model	TAL-046-E   HCI444D/S4L1DD41
Number of Poles	4
Winding Pitch	2/3
Insulation Class - Temp Rise	Н
Ingress Protection Rating	IP 23
Excitation System	SHUNT
AVR Model	R120

#### **COMPLY WITH STANDARDS**

ISO 3046, BS 5514, DIN 6271, NEMA-MGI, DIN EN, BS 5000, IEC 60034,IEC 60947-2

ALTERNATOR OPERATING DATA		
Over speed	2250 rpm	
Voltage Regulation	<u>+</u> 1%	
Harmonic Coefficient THF	< 3.5%	
Tel. influence TIF	< 50	
Cooling air flow	0.25 m3/ Sec	

#### **Standard Specifications:**

#### 6- Fuel Tank:

Capacity of fuel tank is for 8-10 hours Built in fuel tank up to 800 kVA

#### 7- Circuit Breaker:

LS

#### 8- Control system alarms:

- Over and Under Speed
- Low and High Battery Volt.
- Start and Stop Failure
- **Over Current**
- Under / Over Generator Voltage
- Low Oil Pressure
- **Emergency stop**
- High engine temperature

#### 9- Warranty policy:

- AQT GENERATOR products has a warranty for 12 Months or 1000 hours whichever occurs first against any manufacturing defects
- Wearing parts (filters), incorrect man made operation, maintenance failures are excluded from the warranty policy

#### **Acoustic Enclosure Specifications:**

Enclosure Type	Acoustic & Weather Proof
Drainage Provision	Fuel and Water Drainage
Transportation	Tested Single Point Lifting Facility & Forklift Pockets
Ingress Protection Rating	IP 23
Lifting	ISO Standard Lifting
Canopy RAL Color	TAL 9010
Base frame RAL Color	RAL 9011
Noise Pressure level @ 7m 66db(A) @ 7mt	

## **Control System:**

Large back-lit text display

Multiple display languages

**DSENET** expansion compatible

Data logging facility

Fully configurable via PC using USB communication

Front panel configuration

Efficient power save mode

3 phase generator sensing

Accumulated power monitoring (kWh, kVA h, kVA h)

Generator/load current monitoring and protection (kW)

Breaker contol via fascia buttons

Fuel and start outputs, configurable using can

4 configurable DC outputs

4 configurable analogue/digital inputs

Automatically transfers between mains (utility) and generator

Increased input and output expansion capability via dsenet

IP65 rating (with optional gasket) offers increased resistance to water ingress

Digital inputs; Analogue Inputs



#### DSE 6120

**AUTO START & AUTO MAINS** FAILURE CONTROL


Туре	Length (rom)	Width (mm)	Height (mm)	Fuel Tank (L)	Weight (KG)
OPEN	2400	775	1375	190	1200
CLOSED	2750	1100	1495	190	1810







# Engine:



COOLPAC PERFORMANCE DATA		
Cooling System Design	Air-Air Charge Cooled	
Coolant Ratio	50% ethylene gylcol; 50% water	
Coolant Capacity (L)	55.5	
Limiting Ambient Temp.	55 Degree Celsius	
Fan Power (kWm)	15	
Cooling Fan Air Flow	10	
Air Cleaner Type	Light duty dry replaceable element with restriction	
	indicator	

FUEL CONSUMPTION 1800 (60 HZ)	
Fuel Consumption @ 110%	70
Fuel Consumption @ 100%	63
Fuel Consumption @ 75%	46
Fuel Consumption @ 50%	31
Fuel Consumption @ 25%	18

# Optional configurations:

Engi	ne accessories:			
	Heavy-duty air filter			
П	Coolant heater			
ŏ	Lubricant oil heater			
ă	Fuel and Water Separator			
	Lube oil rotary pump			
	tube on rotary pump			
Alte	rnator And Accessories:			
	Leroy somer/stamford			
	Anti condensation heater			
	PMG + AVR $\diamondsuit$ Double bearing			
Ō	alternator High voltagekV			
ŏ	RTDs for Bearing and winding			
ш	Tribs for bearing and winding			
Coo	ling System:			
П	55 degree Radiator			
=				
	Remote Radiator			
Con	trol System:			
_				
П	AMF			
П	Parallel			
П	Practical type in low temperature environment			
П	Control Screen Heater			
П	Remote Annunciators			
	Other (ComP, DEIF)			
ш				
Circ	rcuit Breaker:			
	3/4 poles			
П	Fixed/handcart type			
Н	Electric mechanism			
_	Electric mechanism			
Aut	omatic Transfer Switch (ATS):			
	ATS cabinet			
	Contractor type ATS			
	Motorized changeover type ATS			
61	I Politica			
_	t Battery:			
	Nickel-cadmium battery			
П	Maintenance-free battery			
ŏ	Battery charger and selector switch			
П	Charging current meter			
Evrho	and Fire Tank			
_	ernal Fuel Tank:			
Ш	Single /double wall fuel tank (500-5000 L)			
П	Fuel Transfer pump			
Exha	aust Muffler:			
	Residential grade			
	Critical grade			
	Hospital grade			
	ilable for voltages :			
П	400/230V, 480/277V, 380/220V, 440/254V,			
	A16/2A0V 220/127V 208/120V			

#### **Our Success**

We owe our success to our hardworking, highly skilled and committed employees. Our core focus lies in providing customized integrated products and services with well-established infrastructure, equipment and manpower to support and provide the turn key solutions for various industries. We provide the latest in power generator technology equipment, allowing us to give our customers the best product and the best possible service.

#### **Objectives**

Our objective is to serve customers to the utmost by providing them with the best-in-class electric generators, reliable door to door delivery, and after sales service at competitive market prices.

"We continue to build our solid reputation for excellence and response, while delivering reliable and tailored solutions to meet the customer's requirements".



At AQT Generators, we take pride in being a dynamic force in the realm of diesel generator sets, offering an extensive range of international brands renowned for their reliability and performance. Our commitment to excellence is reflected in our partnerships with world-famous engine manufacturers such as Perkins and Cummins, coupled with top-notch alternators from Stamford and Leroy Somer.





### **CONTACT US**

Office 204, Al Owais Building, Port Saeed, Plot No. 388-0, Dubai, UAE Call Us: +971 4 547 1703

Email: info@agtgenerators.com

#### FOLLOW US ON OUR SOCIAL MEDIA ACCOUNTS











